

Product Data Guide: Pressure Treated Wood Stain 2000 Series - 250 VOC

SUPERDECK® Pressure Treated Wood Stain has been uniquely formulated to transform pressure treated wood from its original color to natural wood tones while accentuating its distinctive grain pattern. Transparent iron oxide pigments provide a rich, warm appearance and protects against harmful UV rays, while the three oil system and highly effective mildewcides protect against water damage and mildew stains. Product is resistant to foot traffic patterning and will not track.

USES: All exterior pressure treated and non-treated wood.

COLORS:

DB 2001-CEDAR

DB 2005-HEART REDWOOD

DB 2007-CANYON BROWN

DB 2010-NATURAL

DB 2014-VALLEY

DB 2016-GOLDEN OAK

VOC: 250

PRODUCT HIGHLIGHTS:

- One Coat Coverage
- Penetrating 3-Oil System
- Maximum Grain Clarity
- Use on All Exterior Wood

SURFACE PREPARATION: DO NOT APPLY OVER SEALED SURFACES. Remove previous oxidized stains with Superdeck® Wood Cleaner. **NEW WOOD** that has not been kiln dried must be allowed to season 2 to 4 weeks before applying product. Dry time will vary depending on weather and moisture content of wood. Wood may be clean enough to directly apply stain. If not, or if wood has mill glaze, clean redwood and cedar surfaces with Superdeck® Wood Brightener; clean pressure treated wood surfaces with Wood Cleaner. **WEATHERED WOOD** should be free from dirt and other foreign materials. Thoroughly clean all wood surface types with Wood Cleaner and rinse. For redwood and cedar, follow with Wood Brightener to remove tannin stains and brighten wood to its original color.

NOTE: This product is lead free. **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800- 424-LEAD or log on to www.epa.gov/lead.

PRODUCT PREPARATION: Product should be shaken or stirred before and during application.

THINNING: None required.



APPLICATION METHODS: Product may be brushed, rolled or sprayed. If sprayed, use the lowest possible pressure needed for a reasonable spray pattern. Back rolling is suggested when spraying, working the product smoothly and evenly into the wood. This will decrease the possibility of pools or puddles on the surface and ensure a properly penetrated finish.

APPLICATION: Proper application is essential in order to accomplish the full benefits of product appearance and performance. Different wood species, textures and natural color will affect finished shade. Always test a small area first for color satisfaction before coating entire project. Pressure Treated Wood Stain is a penetrating stain that must be applied only at a rate the wood will absorb. Do not pool or puddle product on surface. Excess product allowed to sit on surface will result in a tacky finish and extended dry time. Remove tacky finish with mineral spirits within 24 hours of application or with a mild solution of Wood Cleaner after 24 hours. When properly applied, the wood surface will have a positive dry and the wood fibers beneath the surface will maintain excellent lubrication. Thoroughly coat the porous ends of all boards with product.

NUMBER OF COATS: One coat depending on wood porosity and wood moisture content.

APPLICATION TEMPERATURE: 40° F.–95° F. Do not apply if wood surface is hot to touch or if rain is likely to occur.

DRY TIME @ 77° F: 8 hours to touch, 24 hours for traffic; depending on weather conditions.

SPREAD RATE: Approximate spread rate: Smooth Surfaces: 250–350 sq. ft./gal.; Rough Sawn: 150–250 sq. ft./gal.

STORAGE: Pour remaining product into smaller container to reduce skin forming on product. If skin does form, remove it and strain product before re-use.

CLEAN UP/DISPOSAL: Clean brushes and equipment with mineral spirits. Dispose of empty container or unused portion in accordance with local, state, and federal regulations. Soak oily rags, steel wool, roller covers, and other stain soaked materials in water after use to avoid spontaneous combustion.

DANGER! AVOID SPONTANEOUS COMBUSTION: Product contains drying oils (linseed oil & tung oil). Rags, steel wool, roller covers, or any other waste soaked with product may spontaneously catch fire if improperly discarded. Immediately after each use, place rags, steel wool, roller covers, or any other waste in a sealed water-filled metal container.

CONTAINS PETROLEUM DISTILLATE. Keep away from heat, sparks and flame. May be irritating to eyes and skin. Do not use product indoors, for exterior use only. Avoid breathing vapors or mist. Use only in areas with adequate ventilation. Wear a vapor/mist respirator during spray applications. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC23C or equivalent) or leave the area. Close container after each use. While using do not eat, smoke or drink. Wear protective clothing, gloves and goggles. Do not use on surfaces intended for food, feed, potable water, livestock or dairy animals.

FIRST AID: If swallowed, do not induce vomiting. Call a physician immediately. In case of eye contact, flush immediately with plenty of water for at least fifteen minutes and get medical attention; for skin,



wash thoroughly with soap and water. Remove contaminated clothing and wash before reuse. Call a physician if any irritation persists.

WARNING: This product contains chemicals known to the state of California to cause cancer, birth defects or other reproductive harm. Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

KEEP OUT OF REACH OF CHILDREN

SPECIFICATIONS:

<i>MATERIAL:</i>	Tung oil (China wood oil), Linseed oil, highly refined Paraffin oil
<i>SOLVENT:</i>	Mineral Spirits
<i>PIGMENT:</i>	Transparent oxide (hydrated ferric oxides)
<i>TYPICAL LBS. /GAL.</i>	7.14
<i>SPECIFIC GRAVITY:</i>	0.86
<i>VISCOSITY:</i>	15 SEC. #2 Zahn cup at 77° F.
<i>TOTAL SOLIDS by WEIGHT:</i>	60%
<i>TOTAL VOLATILE by WEIGHT:</i>	40%
<i>V.O.C.:</i>	Less than 250 grams/liter (ASTM D-2369)
<i>FLASH POINT:</i>	111° F. (T.C.C)
<i>D.O.T. CLASSIFICATION:</i>	Combustible Liquid

GUARANTEE: If you are not completely satisfied with the performance of this product after applying according to label directions, we will replace the product or refund the purchase price at the manufacturer's option. Proof of purchase, complaint description, and photograph required. Manufacturer's liability limited to refund of purchase price or product replacement. In no event shall manufacturer be responsible for labor, personal injury, or damage.

