

LOOP SIZES & LOOP CHARACTERISTICS

LOOP SIZE	LOOP SIZE (FT)	INDUCTANCE	TURNS	DETECTION HEIGHT
6	20	78	2	4.8
6	22	84	2	4.8
6	24	90	2	4.8
6	26	96	2	4.8
6	28	102	2	4.8
6	30	108	2	4.8
6	32	114	2	4.8
6	33	117	2	4.8
6	34	120	2	4.8
6	36	126	2	4.8
6	38	132	2	4.8
6	40	138	2	4.8
8	4	120	4	3.2
8	6	140	4	4.8
8	8	96	3	5.6
8	10	108	3	5.6
8	12	120	3	5.6
8	14	132	3	5.6
8	16	144	3	5.6
8	18	78	2	5.6
8	20	84	2	5.6
8	22	90	2	5.6
8	24	96	2	5.6
8	26	102	2	5.6
8	28	108	2	5.6
8	30	114	2	5.6
8	32	120	2	5.6
8	33	123	2	5.6
8	34	126	2	5.6
8	36	132	2	5.6
8	38	138	2	5.6
8	40	144	2	5.6

Serial Resistance: between two lead-in wires - less than 5 ohms

Leakage to Ground: between one lead-in wire and the ground more than 10 mega ohm at 500 VDC for one minute. Use DI 6200 insulation tester or equivalent

ALL THE NUMBERS ARE APPROXIMATED, ACTUAL RESULTS MAY VARY